

JS005821510A

United States Patent [19]

Cohen et al.

[11] **Patent Number:** 5,821,510

[45] **Date of Patent:** Oct. 13, 1998

[54] LABELING AND TRACING SYSTEM FOR JUMPER USED IN AN EXCHANGE

[75] Inventors: Leonard George Cohen, Atlanta;

George Frank DeVeau, Cumming,

both of Ga.

[73] Assignee: Lucent Technologies Inc., Murray Hill,

N.J.

[21] Appl. No.: 762,258

[22] Filed: Dec. 9, 1996

Related U.S. Application Data

[63] Continuation of Ser. No. 362,292, Dec. 22, 1994, abandoned.


[51] **Int. Cl.**⁶ **G06F 17/00**; G09F 3/00

[52] **U.S. Cl.** **235/375**; 235/385; 79/326; 439/489: 439/491

[56] References Cited

U.S. PATENT DOCUMENTS

1,281,288 1,373,416 2,043,919	10/1918 4/1921 6/1936	Carley 439/491 Everett 439/491 Bengtson 439/491
4,878,610	11/1989	Jove et al
4,934,785	6/1990	Mathis et al
5,103,353	4/1992	Jove et al 360/67
5,122,915	6/1992	Klein et al
5,204,789	4/1993	Jove et al 360/67
5,212,752	5/1993	Stephenson et al 385/78
5,274,729	12/1993	King et al
5,444,579	8/1995	Klein et al 360/67
5,534,818	7/1996	Peterson 327/545
5,588,873	12/1996	Hamai et al 439/491
5,635,868	6/1997	Aiello et al 327/538



OTHER PUBLICATIONS

Advertizement Brochure "LDT 3805/LRT 3800", Portable Data Collection Computer with Laser Scanner/Portable RF Data Collection Computer with Laser Scanner, By Symbol Express, Symbol Express 1995 Catalog (1994).

Brochure on LXE Scanners by Welch Allyn, Data Collection Division, 4619 Jordan Road, Skaneateles Falls, NY 13153–0187 (published Jun., 1994).

Primary Examiner—Donald T. Hajec Assistant Examiner—Drew A. Dunn

[57] ABSTRACT

The present invention includes a system for tracing jumpers used in an exchange to cross-connect optical fibers or wires served by the exchange. The system includes an exchange housing receptacles with optically-encoded data associated with each receptacle or a group of receptacles. The opticallyencoded data for a receptacle(s) uniquely identifies the physical location of the receptacle from any other receptacle in the exchange. Likewise, the jumpers each have opticallyencoded data formed thereon that uniquely identifies the jumper or jumper end and distinguishes the jumper from any other jumper used in the exchange. If no jumper is to be connected to a particular receptacle, a cover with opticallyencoded data can be attached to a receptacle to indicate that no jumper is connected to the receptacle. The system of this invention also includes a handheld optical scanner that can be used by an operator to scan the optically-encoded data associated with a receptacle(s) and the optically-encoded data of a jumper(s) connected to the receptacle(s), and transmits the optically-encoded data signals to a computer of the system of this invention. The computer can generate a display of the physical location of a receptacle(s) in association with the identity of the jumper(s) and connected thereto, so that an operator can diagnose misconnections of the jumpers between receptacles in the exchange.

26 Claims, 6 Drawing Sheets

